

Flexco® SR™ Scalloped Edge™ RAR8 Belt Fastener

RH200



The Flexco® SR™ Scalloped Edge™ RAR8 belt fastener is designed for use on mainline and panel belts with mechanical fastener ratings up to 1500 P.I.W. (263 kN/m).

The 8-rivet pattern, along with the scalloped edge design, ensures quality performance in high-tension applications. The RAR8 also features built-in viewports in each plate for accurate positioning, and the field-proven SR application method for reliable installation and trouble-free tooling.

For questions regarding RAR8 and your application, please contact the Flexco Marketing or Engineering departments.

Rivet Selection Chart

Fastener Size	Belt Thickness Range		Rivet Size
	in.	mm	
RAR8	13/32-7/16	10.5-11	SRC/D
	13/32-1/2	10.5-13	SRD
	15/32-9/16	12-14	SRE
	17/32-5/8	13.5-16	SRF
	19/32-11/16	15-17	SRG



- Lower fastener profile extends belt splice life.
- Reduces maintenance costs.
- Strong holding ability for high tension applications.
- Viewport assures proper installation alignment.



Flexco® Scalloped Edge™

Flexco® SR™ Scalloped Edge™ RAR8 Belt Fastener

Flexco® Scalloped Edge™ RAR8 (Continuous Strip)

Belt Width		Ordering Number
in.	mm	RustAlloy® 400 Series Stainless Steel
48	1200	RAR8-SE-48/1200
54	1350	RAR8-SE-54/1350
60	1500	RAR8-SE-60/1500
72	1800	RAR8-SE-72/1800
84	2130	RAR8-SE-84/2130

Hinge Pins For RAR8

Belt Width		Ordering Number	
in.	mm	ACS6 (3/8" dia.) Bare Armored Stainless Cable*	
		Each (One Pin)	Package (Ten Pins)
48	1200	ACS6-48-1	ACS6-48
54	1350	ACS6-54-1	ACS6-54
60	1500	ACS6-60-1	ACS6-60
72	1800	ACS6-72-1	ACS6-72
84	2130	ACS6-84-1	ACS6-84

* 300 Series



Rivets

Stainless Type 430. Self-setting
pre-assembled with pilot nails.

Ordering Number	
Box (250 Rivets)	Bucket (2000 Rivets)
SRC/D-S	SRC/D-S-2M
SRD-S	SRD-S-2M
SRE-S	SRE-S-2M
SRF-S	SRF-S-2M
SRG-S	SRG-S-2M



MSRT8 Installation Tool

The portable MSRT8 applicator installs R6,
RAR6 and RAR8 fasteners only.

MSRT8 Applicator Complete

Belt Width		Ordering Number
in.	mm	
48	1200	MSRT8-48
60	1500	MSRT8-60
72	1800	MSRT8-72
84	2130	MSRT8-84



RAR8 Anvil Plate



Flexible Steel Lacing Company
2525 Wisconsin Avenue
Downers Grove, IL 60515-4200 U.S.A.
Telephone: (630) 971-0150
Fax: (630) 971-1180
E-mail: advertising@flexco.com
Visit our Web site at: www.flexco.com

Australia: 61-2-9680-3322 • England: 44-1457-891000 • Germany: 49-7428-9406-0 • Mexico: 52-5-674-5326
New Zealand: 64-9-415-4488 • Republic of South Africa: 27-11-974-2771

